



Material Safety Data Sheet

CHEMNOX AN-1076

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name : octadecyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate
CAS number : 002082-79-3
Company name : UV Chem-Keys Co., Ltd
RM9-G, F/9, First Trade Tower, 985# Dongfang RD, Shanghai, China
Zip Code: 200122
Tel: 86 21 58785816
Fax: 86 21 58786585

2. Health Hazards Data

CAS Number : 002082-79-3
Product Name : octadecyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate
Content : 100 %
R-Phrase(s) : R53

3. HAZARDS IDENTIFICATION

May cause long-term adverse effects in the aquatic environment

4. FIRST AID MEASURES (SYMPTOMS)

4. FIRST AID MEASURES (ACTION)

Skin contact : Wash off with soap and plenty of water. Do not use organic solvents
Eye contact : Rinse immediately with plenty of water for at least 15 minutes. In case of eye irritation, seek medical attention.
Ingestion : Immediately give plenty (> 500 ml) of water (if possible charcoal slurry). In case of spontaneous vomiting be sure that vomitus can freely drain due of danger of suffocation. Give water repeatedly. Artificial induction of vomiting should be restricted to first aid staff. Give nothing by mouth in cases of unconsciousness or convulsion. Seek medical advice.
Inhalation : Move to fresh air. In case of irritation of respiratory system or mucous membranes, seek medical attention. In case of indisposition, seek medical attention. In case of prolonged exposure, seek medical attention.



Material Safety Data Sheet

CHEMNOX AN-1076

5. FIRE-FIGHTING MEASURES

- Extinguishing media** : Water spray, Carbon dioxide (CO₂), Foam, Dry powder
- Extinguishing media which must not be used for safety reasons** : High volume water jet
- Exposure hazards** : Contaminated water from fire hoses or sprinklers, etc., must be prevented from draining into watercourses, sewers, or the ground water. Sufficient measures must be taken to retain water used for extinguishing. Contaminated water and soil must be disposed of in conformity with local regulations
- Special protective equipment for firefighters** : Wear full protective clothing. Wear self-contained breathing apparatus
- Hazardous decomposition products** : Oxides of carbon, Toxic gases/vapours

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Do not breathe vapours/dust. Remove all sources of ignition. Avoid contact with skin, eyes and clothing
- Environmental precautions** : Do not flush into surface water, sanitary sewer or ground water system.
- Methods for cleaning up** : Use mechanical handling equipment. Collect the spilled product into suitable containers, which must be tightly sealed and properly labelled. Avoid dust formation.

7. HANDLING AND STORAGE

- Handling** : Handle and open container with care. Avoid dust formation and ignition sources. Ensure good local exhaust ventilation.
Do not eat, drink or smoke at the workplace.
- Storage** : Keep away from food and drink. Store in the original container securely closed.
Protect from heat. Danger! Explosion risk. Risk of explosion if an air-dust mixture forms. Avoid creating dusty conditions.
Empty only into earthed containers. If container is larger than 2000 liter in volume, or when flammable solvents are present inert container or use a system otherwise designed to prevent or contain an explosion -- seek expert advice.



Material Safety Data Sheet

CHEMNOX AN-1076

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limit(s)	: internal exposure limit (8 hour time weighted average) 10 mg/m ³
Technical measures/Precautions	: Exposure limit(s) should be monitored using suitable analytical equipments.
Respiratory protection	: Effective dust mask
Hand protection	: Protective gloves
Eye protection	: Suitable goggles or face protection
Skin and body protection	: Working clothes , Closed footwear

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	: Powder crystalline	
Colour	: white	
Odour	: odourless	
Melting/freezing temperature	: 50 - 55 °C	
Boiling point/range	: not applicable	
Density	: 25 °C 1.02 g/cm ³	
Flash point	: 273 °C	DIN 51584
Ignition Temperature	: 340 °C	BAM
Oxidising properties	: not tested	
Self-ignition temperature	: not tested	
Water solubility	: 20 °C < 2E-4 g/l	
Vapour pressure	: 20 °C 2.5E-7 Pa	
Partition coefficient	: Log Pow > 6	
pH-value	: 5.73	
Explosive properties	: not tested	

10. STABILITY AND REACTIVITY

Decomposition Temperature	: > 350 °C
Conditions to avoid	: Static discharges.
Materials to avoid	: Strong acids, strong bases and strong oxidising agents.
Hazardous Decomposition Products	: Oxides of carbon, Oxides of nitrogen (NOx), Toxic gases/vapours



Material Safety Data Sheet CHEMNOX AN-1076

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity	:	
oral	:	LD50 > 2000 mg/kg
derma	:	not irritant
eye	:	not irritant
skin	:	not sensitizing

12. ECOLOGICAL INFORMATION

Acute toxicity to fish	:	LC50 > 100 mg/l (Zebra fish, 96 hours)	
Acute toxicity to daphnia	:	EC50 > 100 mg/l (Daphnia magna, 24 hours)	EEC C 3
Acute toxicity to bacteria	:	IC50 > 100 mg/l (Sewage sludge, 3 hours)	
Acute toxicity to algae	:	EC50 > 30 mg/l (Scenedesmus sp., 72 hours)	
Biodegradability	:	Partially but not readily	Biodegradable
Biodegradability	:	Do not discharge product unmonitored into the environment.	
Further information	:	Inherently degradable in a combined Zahn-Wellens/Carbondioxid Evolution Test.	

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products	:	Residual chemical should be disposed by incineration or by other modes of disposal in compliance with local legislation.
Contaminated packaging	:	Contaminated packaging material should be treated equivalent to residual chemical. Clean packaging material should be subjected to waste management schemes (recovery recycling, reuse) according to local legislation.

14. Transport information

Flash Point	:	73 °C
ADR/RID Class	:	Free
IMO Class	:	Free
ICAO Class	:	Free



Material Safety Data Sheet

CHEMNOX AN-1076

15. REGULATORY INFORMATION

- EC-Number** : 218-216-0
- Contains** : octadecyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate
- Classification** : Self-classification
- R-Phrase(s)** : R53 May cause long-term adverse effects in the aquatic environment.
- S-Phrase(s)** : S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

16. Other information

- Legal disclaimer** : The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.