Material Safety Data Sheet



NeoCryl A-633

Section 1. Chemical product and company identification

Product name : NeoCryl A-633

Supplier : DSM NeoResins+, Inc. Telephone : +1 (978) 658-6600

730 Main Street Wilmington, MA 01887

USA

Chemical formula : Not applicable.

Material uses : Resin used in the production of coatings, inks and/or adhesives.

Emergency telephone

number

: 800-424-9300 Medical Emergency

For chemical emergency, spill, leak, fire, exposure or accident: call CHEMTREC day or night. DOMESTIC NORTH AMERICA 800-424-9300; INTERNATIONAL, CALL 703-527-3887 (collect calls accepted)

Section 2. Hazards identification

Physical state : Liquid.

Odor : Ammonia. [Slight]

Emergency overview : Caution


SUSPECT CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER. Avoid exposure - obtain special instructions before use. Do not breathe vapor or mist. Contains material which may cause cancer. Risk of cancer depends on duration and level

oi exposure.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29

CFR 1910.1200).

Hazardous Material Information System (U.S.A.)



The PPE (Personal Protection Equipment) designation in the HMIS is provided for use by employees at supplier sites only. Other users of this product are encouraged to evaluate the hazards of the product and assign PPE that is applicable to their specific situations.

Potential acute health effects

Inhalation: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.Skin: No known significant effects or critical hazards.Eyes: No known significant effects or critical hazards.

Potential chronic health effects

Chronic effects : No known significant effects or critical hazards.

Carcinogenicity : Contains material which may cause cancer. Risk of cancer depends on duration and level

of exposure.

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

Medical conditions : None known.

aggravated by over-exposure

See toxicological information (Section 11)

Continued on next page



NeoCryl A-633 Page: 2/6

Section 3. Composition/information on ingredients

CAS number % by weight <u>Name</u> 100-42-5 0.1 - 1styrene

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Section 4. First aid measures

Eye contact : Rinse with plenty of running water. Get medical attention if symptoms occur.

Skin contact : Wash with soap and water. Remove contaminated clothing and shoes. Get medical

attention if symptoms occur.

Inhalation : If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion If swallowed, rinse mouth with water (only if the person is conscious). Get medical attention

if symptoms occur.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is

> suspected that fumes are still present, the rescuer should wear an appropriate mask or selfcontained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before

removing it, or wear gloves.

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

Section 5. Fire-fighting measures

Flammability of the product

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products In case of fire, may produce hazardous decomposition products such as carbon monoxide,

carbon dioxide, (dense) black smoke, aldehydes, organic acids.

Extinguishing media

Suitable : Use water, foam or dry chemical powder.

Special fire-fighting

procedures

: No special measures required.

Protection of fire-fighters : Wear suitable protective clothing. Self-contained breathing apparatus.

Section 6. Accidental release measures

Personal precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

: No special measures required.

Methods for cleaning up

: Absorb spill with inert material (e.g. dry sand or earth) and place in a chemical waste container. Recycle, if possible. Clean up affected area with a large amount of water.

Section 7. Handling and storage

Handling : Use with adequate ventilation.

Store in a fireproof location. Keep away from incompatible materials and avoid specific Storage

conditions (See section 10).

Section 8. Exposure controls/personal protection

Engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Personal protection

Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Continued on next page

NeoCryl A-633 Page: 3/6



Skin : Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before handling

this product.

Respiratory : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard

if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working

limits of the selected respirator.

Hands : Memical-resistant, impervious gloves complying with an approved standard should be

worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the

time to breakthrough for any glove material may be different for different glove

manufacturers. In the case of mixtures, consisting of several substances, the protection

time of the gloves cannot be accurately estimated.

Product name

styrene

Exposure limits

ACGIH TLV (United States, 3/2012).

TWA: 20 ppm 8 hours. TWA: 85 mg/m³ 8 hours. STEL: 40 ppm 15 minutes. STEL: 170 mg/m³ 15 minutes.

OSHA PEL 1989 (United States, 3/1989).

TWA: 50 ppm 8 hours. TWA: 215 mg/m³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 425 mg/m³ 15 minutes.

OSHA PEL Z2 (United States, 11/2006).

TWA: 100 ppm 8 hours.

CEIL: 200 ppm

AMP: 600 ppm 5 minutes.

NIOSH REL (United States, 6/2009).

TWA: 50 ppm 10 hours. TWA: 215 mg/m³ 10 hours. STEL: 100 ppm 15 minutes. STEL: 425 mg/m³ 15 minutes.

Consult local authorities for acceptable exposure limits.

Remarks : If respiratory protection is needed, use a NIOSH certified respirator with an Assigned

Protection Factor (APF) of at least 10.

Section 9. Physical and chemical properties

Physical state : Liquid.

Flash point : Closed cup: >100°C (>212°F) [(estimate)]

Color : White

Odor : Ammonia. [Slight]

pH : 7.9 to 8.5 **Boiling point** : 100°C (212°F)

Specific gravity : 1.03
Vapor density : <1 [Air = 1]

Solubility : Partially soluble in the following materials: cold water and hot water.

Section 10. Stability and reactivity

Stability and reactivity : The product is stable.

Conditions to avoid : Keep away from heat, sparks and flame.

Materials to avoid : No special recommendations.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not

be produced.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Continued on next page



Section 11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
s tyrene	LC50 Inhalation Vapor	Rat	12 g/m³	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	=
	LD50 Oral	Rat	5000 mg/kg	-

Conclusion/Summary

: Not available.

Chronic toxicity

Conclusion/Summary : Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
styrene	Respiratory - Irritant	Mammal - species unspecified	-	-	-

Conclusion/Summary

: Not available.

Sensitizer

Conclusion/Summary

: Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
styrene	A4	2B	-	-	Possible	_

Mutagenicity

Conclusion/Summary

: Not available.

Teratogenicity

Conclusion/Summary

: Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Section 12. Ecological information

Ecotoxicity : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
styrene	Acute EC50 4.9 mg/l	Algae	72 hours
	Acute EC50 4.7 mg/l	Daphnia	48 hours
	Acute LC50 4.02 mg/l	Fish	96 hours
	Chronic NOEC 1.01 mg/l	Daphnia	21 days

Conclusion/Summary

: Not available.

Persistence/degradability

Conclusion/Summary : Not available.

Section 13. Disposal considerations

Waste disposal : Waste must be disposed of in accordance with national and local environmental regulations.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Consult your local or regional authorities.

Page: 5/6

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT Classification	Not regulated.			-		-
TDG Classification	Not regulated.			-		-
Mexico Classification	Mot regulated.			-		-
ADR/RID Class	Mot regulated.	~		-		-
IMDG Class	Not regulated.			-		-
IATA-DGR Class	Mot regulated.	F		-		-

Special precautions for user

ransport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

Clean Air Act Section 112 : Styrene 0.1119

(b) Hazardous Air Pollutants (HAPs)

SARA 313

Product name : styrene

CAS number Concentration 100-42-5 0.1119

Form R - Reporting Supplier notification

requirements

: styrene

100-42-5 0.1119

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations

: Connecticut Carcinogen Reporting: None of the components are listed.

Connecticut Hazardous Material Survey: None of the components are listed.

Florida substances: None of the components are listed.

Illinois Chemical Safety Act: None of the components are listed.

Illinois Toxic Substances Disclosure to Employee Act: None of the components are

Louisiana Reporting: None of the components are listed. Louisiana Spill: None of the components are listed. Massachusetts Spill: None of the components are listed.

Massachusetts Substances: None of the components are listed. Michigan Critical Material: None of the components are listed.

Minnesota Hazardous Substances: None of the components are listed.

New Jersey Hazardous Substances: The following components are listed: STYRENE

MONOMER; BENZENE, ETHENYL-

New Jersey Spill: None of the components are listed.

New Jersey Toxic Catastrophe Prevention Act: None of the components are listed. New York Acutely Hazardous Substances: The following components are listed: Styrene New York Toxic Chemical Release Reporting: None of the components are listed. Pennsylvania RTK Hazardous Substances: The following components are listed:

BENZENE. ETHENYL-

Rhode Island Hazardous Substances: None of the components are listed.

California Prop. 65

WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer.

NeoCryl A-633 Page: 6/6



Ingredient name **Cancer** Reproductive No significant risk **Maximum**

level

acceptable dosage <u>level</u>

acrylonitrile Yes. No. Yes. No.

United States inventory

(TSCA 8b)

: All components are listed or exempted.

Section 16. Other information

: SUSPECT CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER. Label requirements

National Fire Protection Association (U.S.A.)

Fire hazard Reactivity Specific hazard

Date of printing : 12/5/2012. Date of issue : 12/5/2012. Date of previous issue : 11/6/2012.

Version : **2**

Code : 030694WW48574 - USA

Notice to reader

The information contained in the Material Safety Data Sheet is based on our data available on the date of publication. The information is intended to aid the user in controlling the handling risks; it is not to be construed as a warranty or specification of the product quality. The information may not be or may not altogether be applicable to combinations of the product with other substances or to particular applications.

The user is responsible for ensuring that appropriate precautions are taken and for satisfying themselves that the data are suitable and sufficient for the product's intended purpose. In case of any unclarity we advise consulting the supplier or an expert.

Sources of key data : Literature data and/or investigation reports are available through the manufacturer.

Alterations compared to the previous version

: Alterations compared to the previous version are marked with a little (blue) triangle.